

bizhub C364e

- Colour A3 multifunctional
- □ Up to 36 pages per minute

✓ Functionality



– Colour – Black & white



- Black & white - PCL/PS - Local/Network

- USB



- Colour Black & white – Scan-to-eMail – Scan-to-Me
- Scan-to-FTP
- Scan-to-DPWSTWAIN Network
- Scan-to-SMB
- Scan-to-Box - Scan-to-USB
- Scan-to-WebDAV





- Super G3 Fax - PC-Fax – i-Fax














Technology

Emperon™ – print controller	Easily compatible with different users and IT environments through Konica Minolta's unified print technology	/
Simitri® HD – polymerised toner	Delivers high print quality and yet ensures reduced print spending as well as lower environmental impact	/
OpenAPI – solution platform	Server-based applications provide efficient workflows for the entire MFP fleet	/
i-Option – special feature	Offers extended scope and advanced MFP functionality in line with individual requirements	V
CSRC – remote service	Keep productivity up by online device and consumable monitoring by the Konica Minolta service	/
IWS – panel customisation	Improved user-device interaction and enhanced productivity through full MFP panel customisation	/

Option diagram



Finishing options















mixplex/

mixmedia





insertion,

report







sorting



Descriptions

bizhub C364e	A3 multifunctional with 36 ppm b/w and colour.
	Standard Emperon™ print controller with PCL 6c,
	PostScript 3, PDF 1.7 and XPS support. Paper capacity
	of 500 + 500 sheets and 150-sheet manual bypass.
	Media from A6 to SRA3, 1.2 m banner and 52 – 300 gsm.
	2 GB memory, 250 GB hard disk and Gigabit Ethernet
	standard.
DF-624 Document feeder	Reversing automatic document feeder,
	capacity 100 originals
DF-701 Document feeder	Dualscan automatic document feeder,
	capacity 100 originals
OC-511 Original cover	Cover instead of ADF
PC-110 1 x Universal tray	A5-A3, 500 sheets, 52-256 gsm
PC-210 2 x Universal tray	A5-A3, 2 x 500 sheets, 52-256 gsm
PC-410 Large capacity tray	A4, 2,500 sheets, 52–256 gsm
DK-510 Copier desk	Provides storage space for print media and
	other materials
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/4 hole punching, autoswitching
FS-534 Staple finisher	50-sheet stapling, 3,300 sheets max. output
FS-534SD Booklet finisher	50-sheets staple finisher, 20-sheets booklet
	finisher, 2,300 sheets max. output
PK-520 Punch kit for	2/4 hole punching, autoswitching
FS-534/SD	
JS-506 Job separator	Separation for fax output etc.
KP-101 10-Key pad	For use instead of touchscreen
WT-506 Working table	Authentication device placement

FK-511 Fax board	Super G3 fax, digital fax functionality
IC-414 Fiery controller	Professional colour print controller
VI-506 Interface kit for IC-414	Fiery controller interface card
KH-102 Keyboard holder	To place USB keyboard
EK-606 USB I/F kit	USB keyboard connection
EK-607 USB I/F kit	USB keyboard connection, Bluetooth
ID card reader	Various ID card technologies
MK-735 Mount kit	Installation kit for ID card reader
AU-102 Biometric	Finger vein scanner
authentication	
SC-508 Security kit	Copy Guard function (2 kits required if DF-701 is installed
BT-C1e Banner tray	Multipage banner feeding
LK-101v3 Web browser	Web browser and image panel
LK-102v3 PDF enhancements	PDF/A (1b), PDF encryption, digital signature
LK-105v3 OCR text recognition	Searchable PDF and PPTX, PDF/A (1a)
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 Document converter	Generates various file formats incl. DOCX, XLSX and
pack	PDF/A
LK-111 ThinPrint® Client	Print data compression for reduced network impact
UK-204 i-Option Memory	Memory extension for i-Options
UK-208 WLAN for	Required for alternative panel on Android platform
Android panel	
UK-209 DS board for	Required for alternative panel on Android platform
Android panel	(not required if DF-701 is installed)
SX-BR-4600 Wireless LAN	Wireless LAN to network connector

✓ Technical specifications

SYSTEM SPECIFICATIONS

System memory 2,048 MB (standard) System hard disk 250 GB (standard) Interface 10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0 Network protocols TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP Frame types Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP Automatic document feeder (optional) RADF or Dualscan ADF available Printable paper size A6-SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm Printable paper weight 52-300 gsm Standard: 1,150 sheets Max: 3,650 sheets Max: 3,650 sheets Max: 3,650 sheets Tray 1 500 sheets, A5-A3, 52-256 gsm Tray 2 500 sheets, A5-SRA3, 52-256 gsm Tray 3 (optional) 1 x 500 sheets, A5-A3, 52-256 gsm Tray 4 (optional) 2 x 500 sheets, A5-A3, 52-256 gsm Large capacity tray (optional) 150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm Automatic duplexing A5-SRA3; 52-256 gsm
Interface
TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP
SMB; LPD; IPP; SNMP; HTTP
Frame types Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP Automatic document feeder (optional) Up to 100 originals; A6–A3; 35–163 gsm RADF or Dualscan ADF available RADF or Dualscan ADF available Printable paper size A6–SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm Printable paper weight 52–300 gsm Paper input capacity Standard: 1,150 sheets Max.: 3,650 sheets Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Automatic document feeder (optional) Up to 100 originals; A6–A3; 35–163 gsm RADF or Dualscan ADF available Printable paper size A6–SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm Printable paper weight 52–300 gsm Paper input capacity Standard: 1,150 sheets Max.: 3,650 sheets Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
feeder (optional) RADF or Dualscan ADF available Printable paper size A6-SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm Printable paper weight 52-300 gsm Paper input capacity Standard: 1,150 sheets Max.: 3,650 sheets Max.: 3,650 sheets Tray 1 500 sheets, A5-A3, 52-256 gsm Tray 2 500 sheets, A5-SRA3, 52-256 gsm Tray 3 (optional) 1 x 500 sheets, A5-A3, 52-256 gsm Tray 4 (optional) 2 x 500 sheets, A5-A3, 52-256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52-256 gsm Manual bypass 150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm
Printable paper size A6-SRA3, customised paper sizes; banner paper max. 1,200 x 297 mm Printable paper weight 52-300 gsm Paper input capacity Standard: 1,150 sheets Max: 3,650 sheets Tray 1 500 sheets, A5-A3, 52-256 gsm Tray 2 500 sheets, A5-SRA3, 52-256 gsm Tray 3 (optional) 1 x 500 sheets, A5-A3, 52-256 gsm Tray 4 (optional) 2 x 500 sheets, A5-A3, 52-256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52-256 gsm Manual bypass 150 sheets, A6-SRA3, custom sizes, banner, 60-300 gsm
Deanner paper max. 1,200 x 297 mm
Printable paper weight 52–300 gsm Paper input capacity Standard: 1,150 sheets Max.: 3,650 sheets Max.: 3,650 sheets Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Paper input capacity Standard: 1,150 sheets Max: 3,650 sheets Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Max.: 3,650 sheets Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Tray 1 500 sheets, A5–A3, 52–256 gsm Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Tray 2 500 sheets, A5–SRA3, 52–256 gsm Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Tray 3 (optional) 1 x 500 sheets, A5–A3, 52–256 gsm Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Tray 4 (optional) 2 x 500 sheets, A5–A3, 52–256 gsm Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Large capacity tray (optional) 2,500 sheets, A4, 52–256 gsm (optional) 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
(optional) Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Manual bypass 150 sheets, A6–SRA3, custom sizes, banner, 60–300 gsm
Automatic duplaying A5_SRA3: 52_256 gem
Finishing modes Offset; group; sort; staple; punch; centre-fold; letter fold;
(optional) booklet
Output capacity Max.: 3,300 sheets
(with finisher)
Output capacity Max.: 250 sheets
(without finisher)
Stapling Max.: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity Max. 1,000 sheets
Letter fold Up to 3 sheets
Letter fold capacity Max.: 30 sheets (tray); unlimited
Booklet Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity Max.: 100 sheets (tray); unlimited
Copy/print volume Rec.: 25,000 pages
(monthly) Max.1: 125,000 pages
Toner lifetime Black 27,000 pages; CMY 25,000 pages
Imaging unit lifetime Black 120,000 pages/600,000 pages (Drum/Developer)
CMY 90,000 pages/600,000 pages (Drum/Developer)
Power consumption 220–240 V / 50/60 Hz
Less than 1.5 kW (system)
System dimensions 615 x 685 x 779 mm (excl. ADF and lower paper tray unit)
(W x D x H)
System weight Approx. 85 kg

COPIER SPECIFICATIONS

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD polymerised toner
Copy/print speed A4	Up to 36 ppm
(mono/colour)	
Copy/print speed A3	Up to 18 ppm
(mono/colour)	
Autoduplex speed A4	Up to 36 ppm
(mono/colour)	
1st copy out time	5.3 sec.
(mono/colour)	6.9 sec.
Warm-up time	Approx. 20 sec. ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-9,999
Original format	A5-A3
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	Chapter; cover and page insertion; proof copy (print and screen); adjustment test print; digital art functions; job setting memory; poster mode; image repeat; overlay (optional); stamping; copy protection

PRINTER SPECIFICATIONS

Print resolution	1,800 x 600 dpi; 1,200 x 1,200 dpi
Page description	PCL6 (XL 3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
language	
Operating systems	Windows XP (32/64)
	Windows VISTA (32/64)
	Windows 7 (32/64)
	Windows 8 (32/64)
	Windows Server 2003 (32/64)
	Windows Server 2008 (32/64)
	Windows Server 2008 R2
	Windows Server 2012
	Macintosh OS X 10.x
	Unix, Linux, Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Print functions	Direct print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files
	and OOXML (DOCX, XLSX, PPTX); mixmedia and mixplex;
	"Easy Set" job programming; overlay; watermark;
	conv protection: carbon conv print



PRINTER SPECIFICATIONS (OPTIONAL)

Print controller	Embedded Fiery IC-414
Controller CPU	Intel Pentium @ 2.6 GHz
Memory / HDD	2 GB / 160 GB
Page description	Adobe PostScript 3 (CPSI 3019)
language	PCL 6/5c
Operating systems	Windows XP (32/64)
	Windows VISTA (32/64)
	Windows 7 (32/64)
	Windows 8 (32/64)
	Windows Server 2003 (32/64)
	Windows Server 2008 (32/64)
	Windows Server 2008 R2
	Windows Server 2012
	Macintosh OS 9.x/10.x

SCANNER SPECIFICATIONS

Scan speed	Up to 160 ipm (with optional DF-701)
(mono/colour)	op to 100 ipin (mai optional 51 101)
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me)
	Scan-to-SMB (Scan-to-Home)
	Scan-to-FTP
	Scan-to-Box
	Scan-to-USB
	Scan-to-WebDAV
	Scan-to-DPWS
	Network TWAIN scan
File formats	JPEG; TIFF; PDF; PDF/A 1a and 1b (optional); compact PDF;
	encrypted PDF; searchable PDF (optional); XPS; compact XPS;
	PPTX; searchable DOCX/XLSX/PPTX (optional)
Scan destinations	2,100 (single + group); LDAP support
Scan functions	Annotation (text/time/date) for PDF; up to 400 job
	programs; real-time scan preview

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue
	i-Fax
	Colour i-Fax (RFC3949-C)
	IP-Fax
Fax resolution	Max.: 600 x 600 dpi (ultra-fine)
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)
Fax functions	Polling; time shift; PC-Fax; receipt to confidential box;
	Receipt to e-mail/FTP/SMB: up to 400 job programs

USER BOX SPECIFICATION

Max. storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print
	Encrypted PDF print
	Fax receipt
	Fax polling
User box functionality	Reprint; combination
	Download
	Sending (e-mail/FTP/SMB and Fax)
	Copy box to box

SYSTEM FEATURES

Security	ISO 15408 EAL3; IEEE 2600.1 compliant;
	IP filtering and port blocking;
	SSL2; SSL3 and TSL1.0 network communication;
	IPsec support; IEEE 802.1x support; user authentication;
	Authentication log; secure print;
	Hard disk overwrite (8 standard types);
	Hard disk data encryption (AES 128);
	Memory data auto deletion; Confidential fax receipt;
	Print user data encryption; copy protection (Copy Guard,
	Password Copy) optional
Accounting	Up to 1,000 user accounts; Active Directory support
	(user name + password + e-mail + smb folder)
	User function access definition
	Biometric authentication (finger vein scanner) optional
	ID card authentication (ID card reader) optional
Software	PageScope Net Care Device Manager
	PageScope Data Administrator
	PageScope Box Operator
	PageScope Direct Print
	Print Status Notifier
	Driver Packaging Utility
	Log Management Utility

- 1 If the maximum volume is reached within a period of one year, then a maintenance cycle
- ² Warm-up time may vary depending on the operating environment and usage
- All specifications refer to A4-size paper of 80 gsm quality.
 The support and availability of the listed specifications and functionalities varies depending on
- operating systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media
- type, continuous or intermittent printing, ambient temperature and humidity.

 Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

 All brand and product names may be registered trademarks or trademarks of their respective. holders and are hereby acknowledged.































12/2013